

### **OPTIONS**

Omron tamper switch and mercury vibration switch are available as an option. Fixed angle pole top adaptor, heater high security locking system (bi-lock), wall bracket.

Refer to housing Dimensions on page 44.

# APPLICATIONS

Car parks, railway platforms, tunnels, pole mount, wall mount and walkways. Ideal weatherproof general purpose enclosure.

# SMW5PM WEDGE HOUSINGS

Weatherproof pole and wall mount wedge housings. IP66 Outdoor wedge housings for high security applications where corrosion resistance and mechanical strength are required.

The SMW5PM & SMW5PMSS are manufactured from either powder coated zinc plated steel or stainless steel. The pole mounted enclosure allows the angled face of the bracket to offer additional downward tilt for closer, tighter angles of view.

The SMW5PM & SMW5PMSS are attractive, weatherproof enclosures which are also highly vandal, corrosive and tamper resistant.

# SPECIFICATIONS

### Construction

SMW5PM- 2.5mm zinc plated steel. SMW5PMSS- 2.0mm 304 grade stainless steel.

#### Finish

SMW5PM- Mossvale sands (light beige) polyester powder coat. SMW5PMSS- White polyester powder coat.

Lens 6.0mm polycarbonate.

## Access

4 x 6.0mm stainless steel security screws plus one Selectrix coin keylock as standard. Optional bi-lock high security key lock.

Cable Entry 2 x 20mm entries.

Max. Camera Size 265mm.

Weight SMW5PM- 8.6kg.

SMW5PMSS- 7.1kg.



PART NUMBER	DESCRIPTION	
SMW5PM	Fixed tilt weatherproof pole top wedge housing to suit 76.1mm maximum pole diameter.	
SMW5PMSS	Fixed tilt weatherproof pole top wedge housing to suit 76.1mm maximum pole diameter. Stainless steel construction.	
HTR	Heater thermostat to suit all SMW5 housings.	
TSW SMW5	Tamper switch to suit all SMW5 housings.	
BILOCK	High security locking system to suit all SMW5 housings.	